

## Type aM

Calibre (A)	Tension (V)	Pouvoir de coupure (kA)	Réf sans percuteur	Réf avec percuteur	Pkg Pce
<b>10 x 38 mm - HPC</b>					
2	500	120	0.601.02	-	10
4	500	120	0.601.04	-	10
6	500	120	0.601.06	-	10
10	500	120	0.601.10	-	10
16	500	120	0.601.16	-	10
20	500	120	0.601.20	-	10
25	400	120	0.601.25	-	10



## Type gG Industriel

Calibre (A)	Tension (V)	Pouvoir de coupure (kA)	Réf sans voyant	Réf avec voyant	Pkg Pce
<b>10 x 38 mm - HPC</b>					
1	500	120	0.610.01	-	10
2	500	120	0.610.02	0.611.02	10
4	500	120	0.610.04	-	10
6	500	120	0.610.06	0.611.06	10
10	500	120	0.610.10	0.611.10	10
16	500	120	0.610.16	-	10
20	500	120	0.610.20	-	10
<b>14 x 51 mm - HPC</b>					
10	500	120	-	0.613.10	10
32	500	120	0.612.32	-	10
<b>22 x 58 mm - HPC</b>					
20	660	120	0.614.20	-	10
32	660	120	0.614.32	-	10

